# Specialty Resin & Chemical MATERIAL SAFETY DATA SHEET

PRODUCT Cast-a-Mold 25T Silicone Rubber Base

### PRODUCT AND COMPANY IDENTIFICATION

 Specialty Resin & Chemical
 Day: 1-269-462-9256

 58151 Park Place
 Night: 1-269-487-0079

 Dowagiac, Mi 49047
 Poison Hotline: 800-222-1222

**Date prepared:** 03/06/12 **Chemical Type / Description:** 

Silicone Rubber Base

### 2. HAZARDOUS INGREDIENTS

Component % (Approx.) TLV (ppm) CAS No.

None

This product contains Methylpolysiloxanes, which can generate Formaldehyde at approximately 300°F (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin, eye, and throat irritant, is toxic and a potential cancer hazard.

HMIS RATING: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 1

### 3. EFFECTS OF EXPOSURE

**Potential Health Effects:** 

**Ingestion:** Very low toxicity expected. A likely laxative.

**Skin Contact:** None expected.

**Inhalation:** None expected due to very low vapor pressure.

**Eye Contact:** May irritate.

### 4. FIRST AID MEASURES

**Ingestion:** Seek medical attention if adverse symptoms noted.

**Skin:** Remove with dry towel, then wash with soap and water.

**Eyes:** Rinse 15 minutes with running water. Seek medical attention if

irritation persists.

**Inhalation:** Seek fresh air if needed.

**Other:** Not applicable.

### 5. FIRE FIGHTING INFORMATION

Flash Point (Method): >93°C, >200°F

Flammability Class: None.

Flammability Limits in Air: Not available.

**Extinguishing Media**: All standard media for chemical fires.

**Hazardous Combustion Products** CO, CO<sub>2</sub>, SiO<sub>2</sub>, H<sub>2</sub>CO, H<sub>2</sub>O

**Special Fire Fighting Notes:** Like all silicones, Cast-a-Mold 25T can produce formaldehyde when

strongly heated in air.

### ACCIDENTAL RELEASE MEASURES

Pick up spilled material with absorbent clay, then wash area thoroughly with water and detergent. Spilled material is very slippery.

### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes and prolonged skin contact. **Storage:** Store in cool (< 40°C), closed and dry containers.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Good general ventilation.

**Personal Protective Equipment** 

**Eyes:** Safety glasses.

**Skin:** Rubber or plastic gloves as desired.

**Inhalation:** Not normally required.

### PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Fluid paste.

Color: Off White.
Odor: Very slight.
Boiling Point: Will not boil.

**Vapor Density (air = 1):** There is negligible vapor pressure.

Specific Gravity: 1.10
Solubility in Water: None.

### 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable.

Hazardous Polymerization: Will not occur.

**Decomposition Products:** Only in fire conditions, see section 5.

Materials to Avoid: None.

**Conditions to Avoid:** Keep tightly sealed to avoid contamination.

### 11. TOXICOLOGICAL INFORMATION

See section 3.

### 12. ECOLOGICAL INFORMATION

None available

### 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with state and local regulations.

### 14. TRANSPORT INFORMATION

**DOT SHIPPING NAME:** Not regulated.

**DOT HAZARD CLASS:** None. **UN/NA Number:** None.

### 15. REGULATORY INFORMATION

TSCA INVENTORY STATUS: Listed.

**SARA TITLE III / CERCLA** 

SECTION 302 EXTREMELY TOXIC: No. SECTION 304 CERCLA HAZARD: No. SECTION 311 / 312 HAZARD No.

**CLASS:** 

**SECTION 313 TOXIC CHEMICALS:** No.

### 16. OTHER INFORMATION

We believe the above information is correct as of the date of this MSDS. However, as this information and the conditions under which the product are used are beyond the control of Specialty Resin & Chemical, it is the user's obligation to determine the conditions for the safe use of the product. No warranty, expressed or implied, is hereby made.

## **Specialty Resin & Chemical MATERIAL SAFETY DATA SHEET**

**PRODUCT** Cast-a-Mold 25T Silicone Rubber Activator

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Specialty Resin & Chemical

58151 Park Place Dowagiac, Mi 49047

**Date prepared:** 03/09/04 **Chemical Type / Description:** 

Silicone Rubber Activator

Telephone: 269-462-9256

#### 2. HAZARDOUS INGREDIENTS

CAS No. Component % (Approx.) TLV (ppm) Trimethoxyorganosilane 25 200 ppm Trade Secret Organotin compound > 5 0.1 mg/m3 as Sn Trade Secret

**HMIS RATING: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 2** 

#### 3. EFFECTS OF EXPOSURE

**Potential Health Effects:** 

**Ingestion:** Toxic (contains trace amounts of methanol).

**Skin Contact:** Can cause dermatitis.

**Inhalation:** Central nervous system depression.

**Eye Contact:** Will irritate; can cause blindness (methanol).

#### FIRST AID MEASURES 4.

Ingestion: Seek medical attention immediately.

> Skin: Remove with dry towel, then wash with soap and water.

Rinse 15 minutes with running water. Seek medical attention if

irritation persists.

**Inhalation:** Seek fresh air if needed.

**Other:** Not applicable.

#### 5. FIRE FIGHTING INFORMATION

**Flash Point (Method):** > 205 F (Setaflash)

Flammability Class: None.

Flammability Limits in Air: Not available.

**Extinguishing Media**: All standard media for chemical fires.

**Hazardous Combustion Products** CO, CO<sub>2</sub>, SiO<sub>2</sub>, H<sub>2</sub>CO.

**Special Fire Fighting Notes:** Like all silicones, Cast-a-Mold 25T can produce formaldehyde when

strongly heated in air.

### 6. ACCIDENTAL RELEASE MEASURES

Pick up spilled material with absorbent clay, then wash area thoroughly with water and detergent. Spilled material is very slippery.

### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes and skin. Avoid inhalation. Ground container

when transferring.

**Storage:** Store in cool (< 40°C), closed and dry containers. Do not freeze.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Good general ventilation.

**Personal Protective Equipment** 

**Eyes:** Safety glasses.

**Skin:** Rubber or plastic gloves as desired.

**Inhalation:** Not normally required.

### PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Low viscosity liquid.

Color: Green
Odor: Alcohol.
Boiling Point: Not tested.

**Vapor Density (air = 1):** There is negligible vapor pressure.

**Specific Gravity:** 0.98 **Solubility in Water:** None.

### STABILITY AND REACTIVITY

**Chemical Stability:** Will hydrolyze. **Hazardous Polymerization:** Will not occur.

**Decomposition Products:** Only in fire conditions, see section 5. **Materials to Avoid:** Water, acids, bases, oxidizing agents. **Conditions to Avoid:** Keep tightly sealed to avoid contamination.

### 11. TOXICOLOGICAL INFORMATION

See section 3.

### 12. ECOLOGICAL INFORMATION

None available

### 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with state and local regulations.

### 14. TRANSPORT INFORMATION

**DOT SHIPPING NAME:** Not regulated.

**DOT HAZARD CLASS:** None. **UN/NA Number:** None.

### 15. REGULATORY INFORMATION

**TSCA INVENTORY STATUS:** This material or all of its contents are listed on the Toxic

Substances Control Act (TSCA).

### OTHER INFORMATION

We believe the above information is correct as of the date of this MSDS. However, as this information and the conditions under which the product are used are beyond the control of Specialty Resin & Chemical, it is the user's obligation to determine the conditions for the safe use of the product. No warranty, expressed or implied, is hereby made.